

HYD-10-12K-LS1

10 / 12 kW

Single-phase hybrid inverter



High performance

- 2 MPPTs, Max. 40A DC input current per MPPT
- Support 200% overload for 10 seconds
- Max. 190A charge/discharge current



Flexible application

- Multiple inverters in parallel to build a microgrid
- Support diesel generator



Safe & reliable

- AFCI protection integrated
- On/off grid seamless switching (4ms)

Model	HYD-10K-LS1	HYD-12K-LS1
PV Input		
Recommended Max. PV Power	20 kWp	24 kWp
Max. Input Voltage		550 Vd.c.
Start-up Voltage ^[1]		90 Vd.c.
Rated Input Voltage		360 Vd.c.
MPP Voltage Range		60-500 Vd.c.
Number of MPPT		2
Max. Number of Input Strings per MPPT		2/2
Max. Input Current		40/40 A
Max. Isc		50/50 A
Battery		
Voltage Range		40-60 Vd.c.
Number of Battery Input Channels		1
Max. Charging Power		10 kW
Max. Discharging Power	10 kW	12 kW
Max. Charging Current	210 A	250 A
Max. Discharging Current	210 A	250 A
Battery Type ^[2]		Lead-acid or Lithium-ion
BMS Communication		RS-485/CAN
AC Backup		
Rated Output Voltage		L+N+PE, 220/230/240 Va.c.
Rated Output Frequency		50/60 Hz
Rated Output Power	10 kW	12 kW
Rated Output Current	45.5/43.5/41.7 A	50.0/54.5/54.5 A
Rated Apparent Power	10 kVA	12 kVA
Max. Apparent Power	11 kVA	13.2 kVA
Max. Output Current	50.0/47.8/45.8 A	55.0/60.0/60.0 A
Peak Output Apparent Power ^[5]		2 times of rated power, 10s
THDv(@ linear load)		<3%
Switching Time ^[4]		4 ms default
AC Generator		
Rated Input Voltage		L+N+PE, 220/230/240 Va.c.
Rated Input Frequency		50/60 Hz
Rated Input Power	10 kW	12 kW
Rated Input Current	45.5/43.5/41.7 A	50.0/54.5/54.5 A
Rated Apparent Power	10 kVA	12 kVA
Max. Apparent Power	11 kVA	13.2 kVA
Max. Input Current	50.0/47.8/45.8 A	55.0/60.0/60.0 A
AC Grid		
Rated Voltage		L+N+PE, 220/230/240 Va.c.
Rated Frequency		50/60 Hz
Rated Output Power	10 kW	12 kW
Rated Output Current	45.5/43.5/41.7 A	50.0/54.5/54.5 A
Rated Apparent Power	10 kVA	12 kVA
Max. Apparent Power	11 kVA	13.2 kVA
Max. Output Current	50.0/47.8/45.8 A	55.0/60.0/60.0 A
Max. Input Current ^[5]	50A	60A
THDi		<3%
Power Factor Range		0.8 lagging - 0.8 leading
Efficiency		
Max. MPPT Efficiency		99.9%
Max. Efficiency		97.6%
European Efficiency		97.0%
Max. Efficiency of Charging/Discharging ^[6]		95.0%
Protection		
DC Switch		Yes
PV Reverse Connection Protection		Yes
Battery Reverse Connection Protection		Yes
Output Short Circuit Protection		Yes
Output Overcurrent Protection		Yes
Output Overvoltage Protection		Yes
Insulation Impedance Detection		Yes
Residual Current Detection		Yes
Anti-island Protection		Yes
Surge Protection ^[7]		PV: Type II, AC: Type II
General Parameter		
Inverter Topology		Non-Isolation
Protective Class		Class I
IP Rating		IP66
Overvoltage Category		AC III, DC II
Operating Temperature Range		-30°C to +60°C (derating above +45°C)
Relative Humidity Range		5%-95%
Max. Operating Altitude		4000 m (derating above 2000 m)
Standby Self-consumption ^[8]		<15 W
Installation Method		Wall Mounted
Dimensions(W×H×D)		410×620×270 mm
Cooling Mode		Intelligent Airflow
Weight		30 kg
Communication		RS485, Optional: WiFi/4G/LAN
Display		LCD & APP

[1] Minimum PV voltage to start MPPT operation. [2] Please refer to document "SOFAR inverter Model compatible battery list". [3] Full sun and battery.

[4] In the on-grid mode, the nominal power of the hybrid inverter is higher than the total power of the home loads. [5] Continuous AC passthrough current from grid to load.

[6] Battery-AC maximum efficiency of battery charge and discharge. [7] According to EN/IEC 61643-11. [8] Standby loss at rated input voltage.

*All specifications are subject to change without notice.